

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 0 545 423 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:
06.08.1997 Bulletin 1997/32

(51) Int. Cl.⁶: **A61F 13/15**

(21) Application number: **92120677.7**

(22) Date of filing: **03.12.1992**

(54) Body fluid absorbent article

Absorbierender Artikel für Körperflüssigkeiten

Article absorbant pour fluides corporels

(84) Designated Contracting States:
DE FR IT SE

(30) Priority: **04.12.1991 JP 348223/91**

(43) Date of publication of application:
09.06.1993 Bulletin 1993/23

(73) Proprietor: **UNI-CHARM CORPORATION**
Kawanoe-shi Ehime-ken (JP)

(72) Inventors:
• **Yamamoto, Masamitsu**
Kawanoe-shi, Ehime-ken (JP)

• **Murakami, Masaki**
Kinsel-cho, Ehime-ken (JP)
• **Mizutani, Satoshi**
Kawanoe-shi, Ehime-ken (JP)

(74) Representative: **Sperling, Rüdiger, Dipl.-Ing. et al**
Patentanwälte Dipl.Ing. S. Staeger,
Dipl.Ing.Dipl.Wirtsch.Ing. R. Sperling,
Müllerstrasse 31
80469 München (DE)

(56) References cited:
EP-A- 0 040 085 **EP-A- 0 178 108**
EP-A- 0 336 578 **GB-A- 2 055 586**
US-A- 4 798 603

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

Description

BACKGROUND OF THE INVENTION

The present invention relates to an improvement in the body fluid absorbent articles such as sanitary napkins used to absorb and thereby to hold menstrual discharge.

Body fluid absorbent articles such as sanitary napkins of prior art generally comprise a surface structure composed of a topsheet molded from thermoplastic film formed with liquid passages or channels spaced from one another in longitudinal, transverse and diagonal directions of the topsheet, each of these liquid passages or channels being opened at both upper and lower ends thereof, and an absorbent core of which the top surface is covered with the topsheet. Such surface structure can be basically classified into three types as will be described below.

One example of the first type is disclosed in Japanese Patent Application publication No. 1982-17081. A topsheet constituting a surface structure in this patent application is molded from thermoplastic film so that a plurality of liquid passages tapered downward and their lower openings are close in contact with the top surface of an absorbent core. With such arrangement, however, if each liquid passage is tapered downward as extremely as almost to a critical diametric dimension of its lower opening beyond which a quantity of body fluid once absorbed by the absorbent core may partially flow backward again the lower openings of the liquid passages, the lower openings of the liquid passages may be blocked by a clot, assumed that the body fluid is menstrual discharge containing such clot, and no additional discharge can be smoothly transferred into the absorbent core. If the lower openings of the liquid passages are dimensioned so as to avoid this problem, the quantity of menstrual discharge having been absorbed in the absorbent core will be visible for users in a vivid shade and users may feel uncomfortable when she disposes used napkin. With the topsheet made from light-transmissive plastic film such as polyethylene film, the quantity of menstrual discharge having been absorbed in the absorbent core will be visible for users in a relatively light shade through ribs defining the upper openings of the respective liquid passages.

Another example of the first type is disclosed in Japanese Patent Application Disclosure Gazette No. 1989-249502. A topsheet forming a surface structure disclosed therein comprises a thermoplastic film layer laminated on the bottom surface of a thermoplastic fibrous layer. Since this topsheet is of two-layered structure composed of a fibrous layer and a plastic film layer, it never takes place that the quantity of menstrual discharge having been absorbed in an absorbent core is visible for users in a lighter shade through the topsheet. While this topsheet is preferred to the previously mentioned topsheet so far as the shielding effect for menstrual discharge is concerned, there remains the

problem that the quantity of menstrual discharge having been absorbed in the absorbent core is visible for users in a relatively vivid shade through openings of the respective liquid passages.

One example of the second type is disclosed in Japanese Patent Application Disclosure Gazettes Nos. 1986-158954; 1989-119251; and 1990-19153. A topsheet forming a surface structure disclosed therein is molded from hydrophobic plastic film formed with liquid channels having bottoms closed and side walls opened. With such surface structure, the quantity of menstrual discharge having been absorbed in an absorbent core is not visible for users through the liquid channels. However, the closed bottoms of the respective liquid channels function as barriers preventing a sufficient quantity of menstrual discharge from being rapidly transferred to the absorbent core and clots of menstrual discharge, if any, will be apt to cling to the bottoms and stay there, resulting in that these clots are sometimes visible for users in a vivid shade.

One example of the third type is disclosed in Japanese Patent Application Disclosure Gazette No. 1982-89861. A topsheet forming a surface structure disclosed therein comprises a hydrophobic meshy topsheet, a hydrophobic fibrous layer disposed on the bottom surface of said hydrophobic meshy topsheet, and a hydrophobic plastic film layer formed with tapered liquid passages and disposed on the bottom surface of said fibrous layer. This surface structure is normally effective to avoid the problem that the quantity of menstrual discharge having been absorbed in an absorbent core is visible for users through the liquid passages. However, clots of menstrual discharge, if any, may cling to fibres of the meshy topsheet as well as of the underlying fibrous layer and block the meshes, preventing a sufficient quantity of menstrual discharge from smoothly flowing into the liquid passages. In such case, menstrual discharge may be vividly visible for users just as with the above-mentioned second type of surface structure.

In view of such problems, it is a principal object of the invention to provide a surface structure for the article as mentioned in the beginning so improved that, in spite of using a topsheet formed with a plurality of liquid passages, an adequate quantity of menstrual discharge can be rapidly transferred to an absorbent core and the quantity of menstrual discharge having been absorbed in the absorbent core are substantially invisible for users.

SUMMARY OF THE INVENTION

The object set forth above is achieved, in accordance with the invention, by a body fluid absorbent article comprising a topsheet formed with liquid passages spaced from one another in longitudinal, transverse and diagonal directions, each of these liquid passages extending through the thickness of the topsheet so as to be opened at both upper and lower ends, and an

absorbent core of which at least the top surface is covered with the topsheet, characterized by that a meshy sheet composed of fibres defining meshes smaller than lower openings of the respective liquid passages is interposed between the top surface of said absorbent core and the bottom surface of said topsheet in close contact with the lower ends of said liquid passages so that said fibres extend, across the lower openings of the respective liquid passages and thereby divide the respective lower openings into a plurality of openings.

Preferably said meshy sheet is made of hydrophobic plastic film splitted into said fibres.

Preferably said fibres are further splitted into a plurality of finer fibres.

Preferably the lower ends of said liquid passages are bonded integrally to the top surface of said meshy sheet.

Preferably said meshy sheet is treated with suitable surfactant to make it hydrophilic.

Preferably side walls of said liquid passages are partially cut away.

Preferably said topsheet is made of hydrophobic plastic film.

The article constructed according to the invention allows menstrual discharge to be smoothly guided into the liquid passages since there exists no barrier on the top surface of the topsheet which will prevent menstrual discharge from smoothly flowing into the upper openings of the respective liquid passages. The fibres extending across the lower opening of each liquid passage are effective to attenuate or alleviate the shade in which the quantity of menstrual discharge having been absorbed in the absorbent core may be visible for users through the lower opening of the liquid passage and at the same time to suppress the possibility that the quantity of menstrual discharge having been absorbed in the absorbent core can flow back toward the top surface of the topsheet. Such functions can be proportionally improved as the number of the fibres extending across the lower opening of each liquid passage is increased.

Rapid transfer of menstrual discharge from the top surface of the topsheet to the liquid passages and therefore to the absorbent core are not obstructed by the fibres since these fibres are disposed across the lower openings of the respective liquid passages and a diameter of each opening defined by these fibres is smaller than the diameter of each liquid passage.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention will be described more in detail with reference to the accompanying drawings, in which:

Fig. 1 is a perspective view showing an embodiment of a sanitary napkin constructed according to the invention with a portion adjacent one end thereof having been transversely cut off;

Fig. 2 is a perspective view showing another embodiment of the sanitary napkin constructed

according to the invention with a portion adjacent one end thereof having been transversely cut off;

Fig. 3 shows, in an enlarged scale, a part of the surface structure provided according to the invention (A) in a sectional view and (B) in a plan view;

Fig. 4 (A) through (E) shows, in an enlarged scale, various sectional configurations of the liquid passages to be formed in the topsheet constituting a part of the surface structure provided according to the invention, respectively; and

Fig. 5 is a fragmentary plan view showing, in an enlarged scale, the meshy sheet constituting a part of the surface structure provided according to the invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

As shown by Figs. 1 and 2, a sanitary napkin constructed according to the invention generally comprises an absorbent core 1, a liquid-impermeable backsheet 2 disposed on a bottom surface of the absorbent core 1, a meshy sheet 3 disposed on the top surface of the absorbent core 1, and a liquid-permeable topsheet 4 disposed on the top surface of the meshy sheet 3, wherein a portion of the backsheet 2 extending beyond the outer periphery of the absorbent core 1 is bonded to the corresponding portions of the meshy sheet 3 as well as to the topsheet 4 by adhesive or welding means. The napkin shown by Fig. 1 has the meshy sheet 3 covering the inner surface of the topsheet 4 in coextensive therewith while the napkin shown by Fig. 2 has the meshy sheet 3 covering only the top surface of the absorbent core 1.

As will be apparent from Fig. 3 (A) and (B), the topsheet 4 is formed with liquid passages 5 spaced from one another in longitudinal, transverse and diagonal directions thereof, each of these liquid passages extending through the thickness of the topsheet 4, i.e., being opened at both upper and lower ends thereof. Each liquid passage 5 is dimensioned so that its upper opening has a diameter D_1 of 0.2 to 6.55 mm and its lower opening has a diameter D_2 of 1 to 6 mm. The sectional configuration of each liquid passage 5 is not limited to that as illustrated by Fig. 3 and may be any of those as illustrated by Fig. 4. It should be understood that the respective liquid passages 5 arranged in such manner in the topsheet 4 will effectively function even when their sectional configurations are not uniform. In such case, the above-mentioned diametrical dimensions of the upper and lower openings should be understood as the average values. The lower end of each liquid passage 5 preferably has an opening area ratio of 20 to 60%.

Such topsheet 4 can be obtained by any of the methods well known in the art, for example, a method comprising steps of placing thermoplastic film on the top surface of a mold formed with tubular openings which extend therethrough in its thickness direction and

having sectional configurations corresponding to those of the respective liquid passages 5 to be formed, applying a sufficient negative pressure to the bottom surface of the mold to inflate portions of the film surrounded by upper openings of the respective tubes downward until these portions thus inflated like balloons burst at their bottoms while the film is heated up to its softening point, and finally curing the film. The bottom edge of each liquid passage 5 formed as a result of said burst under the negative pressure may be somewhat rugged depending on the particular condition of molding and, if desired, such rugged bottom edge may be trimmed off or burnt off in the well known manner. The liquid passages 5 shown by Fig. 4(E) have their side walls intentionally notched to obtain rugged lower edges.

The topsheet 4 may be made from thermoplastic material such as polyethylene, polypropylene, EVA, nylon or styrene or a mixture thereof. Filler such as titanium dioxide or calcium carbonate of 1 to 10% by weight may be added to the thermoplastic material in order to lower a light-transmissivity thereof so as to obtain a weight per unit area of 15 to 40g/m². If desired, the topsheet 4 may be coated with suitable surfactant or such surfactant may be mixed into the starting material of the topsheet 4.

It will be apparent from Fig. 5 that the meshy sheet 3 is composed of plural fibres 6. The meshy sheet 3 can be obtained by any of the well known methods, for example, a method comprising steps of providing thermoplastic film with a plurality of slits or dot-like embosses and then splitting the film into a plurality of fibres 6 by stretching the film both in length and width with or without heating. Alternatively, the meshy sheet can be also obtained by mixing the thermoplastic resin with suitable foaming agent and then splitting this into plural fibres 6 under the effect of said foaming agent while the thermoplastic resin is extrusion-molded into film. A diameter of each opening defined by the fibres 6 must be smaller than the diameter D₂ of the lower opening of each liquid passage 5 and preferably less than a third of the diameter D₂. The fibres 6 may be further splitted or branched into finer fibres. Unlike fibrous web such as nonwoven fabric in which the individual fibres are complicatedly intertwined, crossed, bonded or welded together so as to result in a relatively high weight per unit area, the meshy sheet 3 preferably composed of the fibres 6 so arranged that substantially no liquid is held between the fibres 6. While the fibres 6 of the meshy sheet 3 are shown as in irregular arrangement, the fibre arrangement may also be in a regular pattern. If desired, the meshy sheet 3 may be treated with conventional surfactant to improve its permeability for body fluid such as menstrual discharge.

While the meshy sheet 3 may be made from the material providing the same effect as the topsheet 4, it is preferred to achieve a weight per unit area of 3 to 20g/m² and an apparent thickness of 0.05 to 0.15 mm. It should be understood that it is difficult to make such superthin meshy sheet from fibrous web.

This meshy sheet 3 is placed under the topsheet 4 in close contact with the lower ends of the respective liquid passages 5 and, if desired, said lower ends may be partially bonded integrally to the meshy sheet 3 by adhesive or welding means. In this manner, as will be apparent from Figs. 3(B) and 5, several fibres 6 extend across the lower opening of each liquid passage 5 so as to divide this opening into a plurality of openings. Consequently, menstrual discharge flowing into the liquid passages 5 is then transferred to the absorbent core 1 through these divided openings.

The absorbent core 1 and the backsheet 2 may be made from the material conventionally used in sanitary napkins of prior art for these components. For example, the absorbent core 1 may be made from fluff pulp mixed with superabsorbent polymer powder and, if desired, covered at least on top and bottom surfaces with liquid-permeable sheets such as tissue paper while the backsheet 2 may be made from plastic film, lamination of such plastic film and nonwoven fabric, or water-repellent or water-proof nonwoven fabric.

As has already been mentioned, the article of the invention is advantageous over the conventional article of this art in that the shade in which the quantity of menstrual discharge having been absorbed in the absorbent core may be visible for users through the openings of the liquid passages so as to eliminate uncomfortable feeling which otherwise will be given to users and the quantity of menstrual discharge having been absorbed in the absorbent core is well prevented from flowing back toward the top surface of the topsheet so as to eliminate a sense of wetting for users. The invention easily achieves such effect merely by a unique design of the liquid passages formed in the topsheet, which has been very difficult in the prior art. The article of the invention allows clots of menstrual discharge, if any, to flow into the liquid passages so far as these clots are smaller than the upper openings of the liquid passages, since the upper openings of the liquid passages are covered with no other material.

Claims

1. A body fluid absorbent article comprising a topsheet (4) formed with liquid passages (5) spaced from one another in longitudinal, transverse and diagonal directions of the topsheet, each of these liquid passages extending through the thickness of the topsheet so as to be opened at both upper and lower ends thereof, and an absorbent core (1) of which at least the top surface is covered with the topsheet, characterized in that a meshy sheet (3) comprising fibres defining meshes smaller than lower openings of the respective liquid passages is interposed between the top surface of said absorbent core (1) and the bottom surface of said topsheet (4) in close contact with the lower ends of said liquid passages (5) so that said fibres extend across the lower openings of said liquid passages and thereby

divide the respective lower openings into a plurality of openings.

2. The article as recited in Claim 1, wherein said meshy sheet is made of hydrophobic plastic film splitted into said fibres. 5
3. The article as recited in Claim 1, wherein said fibres are further splitted into a plurality of fibres. 10
4. The article as recited in Claim 1, wherein the lower ends of said liquid passages (5) are bonded integrally to the top surface of said meshy sheet (3).
5. The article as recited in Claim 1, wherein said meshy sheet (3) is treated with surfactant to make it hydrophilic. 15
6. The article as recited in Claim 1, wherein side walls of said liquid passages (5) are partially cut away. 20
7. The article as recited in Claim, wherein said top-sheet (4) is made of hydrophobic film. 25

Patentansprüche

1. Körperflüssigkeit absorbierender Artikel, umfassend eine Decklage (4), in der Flüssigkeitskanäle (5) in Längs-, Quer-, und Diagonalrichtung voneinander beabstandet gebildet sind, von welchen jeder dieser Flüssigkeitskanäle durch die Dicke der Decklage verläuft, so daß er sowohl an seinem oberen als auch an seinem unteren Ende geöffnet ist, und einen absorbierenden Kern (1), von welchem mindestens die Oberseite mit der Decklage bedeckt ist, dadurch gekennzeichnet, daß eine Netzlage (3), die Fasern enthält, die Maschen bilden, welche kleiner sind als die unteren Öffnungen der jeweiligen Flüssigkeitskanäle, zwischen die obere Oberfläche des absorbierenden Kerns (1) und die untere Oberfläche der Decklage (4) in engem Kontakt mit den unteren Enden der Flüssigkeitskanäle (5) gelegt ist, so daß die Fasern quer über die unteren Öffnungen der Flüssigkeitskanäle verlaufen und dadurch die jeweiligen Öffnungen in eine Vielzahl von Öffnungen unterteilen. 30 35 40 45
2. Artikel nach Anspruch 1, bei welchem die Netzlage aus hydrophober Kunststoffolie hergestellt ist, die in die Fasern aufgeteilt ist. 50
3. Artikel nach Anspruch 1, bei welchem die Fasern weiter in eine Vielzahl von Fasern aufgeteilt sind.
4. Artikel nach Anspruch 1, bei welchem die unteren Enden der Flüssigkeitskanäle (5) einstückig mit der oberen Oberfläche der Netzlage (3) verbunden sind. 55

5. Artikel nach Anspruch 1, bei welchem die Netzlage (3) mit einem oberflächenaktiven Mittel behandelt ist, um sie hydrophil zu machen.

6. Artikel nach Anspruch 1, bei welchem die Seitenwände der Flüssigkeitskanäle (5) teilweise ausgeschnitten sind.

7. Artikel nach Anspruch 1, bei welchem die Decklage (4) aus hydrophober Folie hergestellt ist.

Revendications

1. Article absorbant pour fluides corporels, comprenant une feuille de couverture (4) dans laquelle sont ménagés des passages de liquide (5) espacés les uns des autres dans les directions longitudinale, transversale et diagonale de la feuille de couverture, chacun de ces passages de liquide s'étendant au travers de l'épaisseur de la feuille, pour s'ouvrir à la fois sur les faces supérieure et inférieure de celle-ci, et un corps central absorbant (1) dont au moins la surface supérieure est recouverte de la feuille de couverture, caractérisé en ce qu'une feuille réticulée (3) comprenant des fibres définissant des mailles plus étroites que les orifices inférieurs des passages de liquide, est interposée entre la surface supérieure du corps central absorbant (1) et la surface inférieure de la feuille de couverture (4), en contact étroit avec les extrémités inférieures des passages de liquide (5), de sorte que ces fibres s'étendent au travers des orifices inférieurs desdits passages de liquide et divisent ainsi les orifices inférieurs respectifs en une pluralité d'orifices.
2. Article selon la revendication 1, dans lequel la feuille réticulée est fabriquée dans un film plastique hydrofuge fractionné pour former les fibres précitées.
3. Article selon la revendication 1, dans lequel les fibres précitées sont encore fractionnées en une pluralité de fibres.
4. Article selon la revendication 1, dans lequel les extrémités inférieures des passages de liquide (5) sont liées solidairement à la surface supérieure de ladite feuille réticulée (3).
5. Article selon la revendication 1, dans lequel la feuille réticulée (3) est traitée avec un agent de surface pour la rendre hydrophile.
6. Article selon la revendication 1, dans lequel des parois latérales des passages de liquide (5) sont partiellement découpées.
7. Article selon la revendication, dans lequel la feuille

de couverture (4) est fabriquée dans un film hydrofuge.

5

10

15

20

25

30

35

40

45

50

55

FIG.1




FIG.2






FIG.3A**FIG.3B**

FIG.4A




FIG.4B




FIG.4C




FIG.4D




FIG.4E




FIG.5